



Timbond Fast Drying D2 PVA Adhesive + UV Dye

TYPICAL PROPERTIES (at manufacture):

Viscosity:	114 Poise Brookfield 7/20/20 degrees centigrade
PH:	4.6
Solids:	63%
S.G.:	1.13 g/cc 20/20 degrees centigrade
Colour:	White
Shelf life:	6 months
Storage:	In original closed containers at room temperature. DO NOT FREEZE.

APPLICATIONS: Timbond Fast Drying D2 Adhesive is an exceptionally fast setting woodwork assembly adhesive. It bonds a wide variety of sawn and plain woods, plus all the synthetic and naturally derived panel stocks (except cement/silicate board). It is used for assembly blocking-in, frame assembly and other furniture fixing operations, also for hot press work where high hot track and fast bonding is needed, e.g., in edge-lipping and core-stock bonding (e.g. Torevga machine). It contains a UV dye enabling the glue line to be visible under UV light.

Cleaning - Clean down with warm water.

This information is based on our current knowledge of the subject and on technical data that Adkwik Industrial Supplies believes to be reliable

Adkwik | 57 Ditton Walk | Cambridge | CB5 8QD

T. 01223 412373 | F. 01223 249085 | E. sales@adkwik.co.uk | www.adkwik.co.uk